



SUPER HDB ULTRA 20W40



Multigrade diesel engine oil.

APPLICATIONS

- For all naturally aspirated or super charged diesel engines operating under severe conditions.
- Can be used for old vehicles (on road, off road) and DG sets.

SPECIFICATION

- API CF4/SG
- MACK T8A
- IS 13656 :1993 EDL3

ADVANTAGES

- Render very good viscosity stability during operation thus provide required protection of an engine
- Demonstrate resistance against soot agglomeration thus avoids oil thickening
- Excellent antiwear and anti corrosion properties reduces down time and part replacement
- Higher reserve alkalinity helps to neutralize the acids thus extend the drain interval
- Infused with antioxidant, antirust, antifoaming additive for a smoother and trouble free operation

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	SUPER HDB ULTRA 20W40
Density at 29.5°C, kg/l	D 4052	0.874
Kinematic viscosity at 100°C, cSt	D 445	14.97
Viscosity Index	D 2270	112
Pour point, °C	D 97	-24
Total Base Number, mg KOH/g	D 2896 (B)	8.52
Flash point COC, °C	D 92	246

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from : www.total.co.in
Date 01/12