

QUARTZ SMC 0W20



Synthetic technology based multigrade oil for passenger car engines

APPLICATIONS

- Premium quality synthetic technology lubricant designed to meet the demands of today's highest performance gasoline cars.
- Give superior performance in all modern gasoline engines made by Maruti Suzuki
- Recommended for use in arduous service condition experienced in city traffic/ motorway/express highway.
- Intended for lubricating gasoline engines of recent technologies meeting euro IV and BS III pollution control standard

SPECIFICATION

OEM Credentials

- API SN
- Maruti Suzuki

ADVANTAGES

- Balanced formula – Lower viscometrics coupled with superior technology helps to achieve fuel economy without compromising engine durability
- Selective polymer infusion helps in cold starts (faster fluidity) as well as at high temperature to give proper fluid film (Viscous enough) for adequate protection against wear thus helps in ease of operation and enhances power output
- Excellent oxidation resistance coupled with synthetic technology render proper lubrication throughout oil life, thus reduces deposit on piston groove, skirt area. Prevent ring sticking and protects filter against the blockage. Thus helps to exhibit longer drain intervals.
- Higher thermal stability avoids cracking of oil and control sludge formation thus ensuring proper lubrication during hot summer
- Built in friction modifier characteristic protects the engine most sensitive parts from wear and seizure

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be downloaded from : www.total.co.in

Date 01/12

QUARTZ SMC 0W20



TYPICAL CHARACTERISTICS	TEST METHOD ASTM	QUARTZ SMC0W20
Density at 29.5°C, kg/l	D 4052	0.8518
Kinematic viscosity at 100°C, cSt	D 445	8.28
Viscosity Index	D 2270	171
Pour point, °C	D 97	-48
Total Base Number, mg KOH/g	D 2896 (B)	8.1
Flash point COC, °C	D 92	234

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be downloaded from : www.total.co.in

Date 01/12